

**Dhalop Chemicals** 

Sales Division: +91-9820034078

dhalopchem@gmail.com

## **Technical Data Sheet**

## **DCBA-20**

## **General**

**Chemical Composition** 

Higher polyethylene polyamines approx. 55% (isomers of TETA, TEPA, PEHA, and higher)

Alkanolamines approx. 45%

(AEEA, DEA, Hydroxyethyl DETA, and higher)

CAS No.: 84238-53-9/68910-05-4 EINECS No.: 282-508-4/272-729-4 DCBA-20 is a blend of higher polyethylene polyamines and alkanolamines. DCBA-20 is used as an intermediate in the manufacture of asphalt additives, in polyamide resins and corrosion inhibitors. It is also used as a cement grinding agent and flotation agent.

## **Sales Specification**

Characteristic	Unit	Specification	Methods of Analysis
Appearance	-	Dark brown liquid	200
Amine number	mgKOH/g	min 1100	234
Water	w%	max 1.0	305
Viscosity	mPa.s at 50°C	max 100	589

Methods of Analysis are available upon request.

In case of dispute, the listed Method of Analysis will be used as reference methods.

Physical and Chemical Properties					
Property	Value	Property	Value		
Form	viscous liquid	рН	12 at 25 % solution		
Colour	brown	Melting point/freezing point	< -30 °C at 1 013 hPa		
Odour	ammoniacal	Boiling point/boiling range	254 °C at 1 013 hPa		
Flammability (liquids)	Not classified as a flammability hazard	Flash point	176 °C at 1 013 hPa Method: Pensky-Martens ISO 2719		
Explosive properties	Not explosive	Auto-Ignition temperature	355 °C at 1,013 hPa		
Oxidizing properties	The substance or mixture is not classified as oxidizing	Vapour pressure	0,00009 hPa at 20 °C		
Water solubility	Soluble at 20 °C	Relative density	1,024 at 20 °C		
Solubility in other solvents	Soluble in ethanol and acetone	Partition coefficient: n- octanol/water	log Pow: -2,6 at 25 °C		
		Viscosity, dynamic	40 mPa.s at 50 °C		